Pycnomatic ATC For solids and powders density



The first multi-volume gas pycnometer with integrated automatic temperature control



Building materials



Pharmaceuticals



Soils, rocks, mining



Powder materials

Polymers, foam



Ceramic materials

Irradiated materials



Pycnomatic ATC Automatic Temperature Control

The Thermo Scientific Pycnomatic is the ultimate development for density measurement of solid materials available. Based on the technique of gas displacement to measure real density of solids and powders, Pycnomatic delivers unrivalled fast and accurate results.

Real density is a fundamental parameter required to complete the characterization of many solid materials and powders. In addition, density analysis by gas displacement technique is a rapid and reliable way to determine the purity of solids, whenever an immediate but precise test is required. This applies to a wide array of technological fields such as: ceramics, mineralogy, geology, pharmaceuticals, metallurgy, pigments, building materials, foams, plastics, polymers, abrasives and catalysts, just to name the most important.

Simple yet effective

Pycnomatic uses mainly helium as a test gas. This features a very small atomic size that can even permeate the extremely narrow pores in a solid sample, permitting the determination of the real volume occupied by the sample. The ratio of the dried sample weight and the volume measured by the Pycnomatic gives the real density of the material. The high thermal conductivity of helium and its ideal gas behavior at around room temperature, make this technique extremely reliable and fast. Whenever helium is not recommended (i.e. for activated carbons) other inert gases like nitrogen can be used.

Built-in accurate temperature control

- The use of an external circulation bath
- Fastest system stabilization
- Reduced analysis time
- Eliminates repeated calibrations
- Permits density investigation at different temperatures
- Unrivalled reproducibility of density results

Built-in multi-volume capability

- Easy choice of the best configuration according to sample volume and nature
- Constant accuracy in a wide range of volumes
- No requirement for instrument modifications
- No requirement for continuous recalibrations





Pycnomatic

Thermo SCIENTIFIC



Features and Benefits

Fully integrated and automated temperature control	Calibrations and measurements are independent from room temperature variations. High reproducibility of results. Fast thermal stability of sample. Eliminate continuous recalibration. No need for an external circulation bath. Save bench space
Utmost precision in temperature control and pressure stabilization	Highly accurate and reproducible results
Real multi-volume analytical capacity	Delivers a constant level of accuracy and reproducibility, virtually independently from the sample volume
Easy and fast chamber volume change	Different density/weight materials can be tested in a short time frame with high precision
Choice of different purging procedures (flow, pulses or vacuum)	Flexible parameter setup producing the best accuracy with solid samples. Choose the best drying procedure for a particular type of material
Large backlit display and comprehensive alpha-numeric keyboard	Fast and easy accessibility to all the pages relevant to the analysis, calibration and instrument parameters. Detailed and comprehensive sample identification. Virtually no training is required for instrument use
Mechanics are detachable from the electronic compartment	The unit is ready to be installed in a glove box for testing irradiated and radioactive materials
Three different communication ports to a PC, balance and a printer	Saves time during sample preparation and report generation. Data processing and data storage in electronic format
Progressive gas load, expansion and discharge	Improves speed in pressure stabilization, no need for filters to prevent powders elutriation by pressure drop, reduced maintenance
Gas loaded first into reference chamber (high pressure), then expanded into sample chamber (low pressure)	Permits the analysis of foams or compressible samples avoiding possible material shrinkage

Utmost flexibility assured by real multi-volume capability

In density measurement, the best accuracy is produced when the measuring chamber volume of a pycnometer matches the available sample volume to be analyzed. When different types of materials have to be tested, a real multi-volume multireference instrument offers the utmost flexibility and accuracy, regardless of the quantity of sample available. Pycnomatic features five different sample chambers, ranging from four to one hundred cubic centimeters. The user can easily change the chamber volumes without any service intervention. The instrument will then select the optimal volume for the reference chamber. Pycnomatic can keep in memory up to three calibration sets for both reference and sample chambers.

Safe analysis of powders and foams

Pycnomatic is uniquely designed to eliminate any risk of valve and tubing contamination, which can occur in analysis of fine powders. In the Pycnomatic the gas pressure is always carefully controlled to prevent sudden pressure changes. In the case of fine powders, venting to atmosphere is performed through a dedicated outlet port that ensures the pressure drops slowly down to atmospheric value without any risk of either sample loss or system contamination. Finally, the pressure applied to the sample is kept at the minimum required to obtain accurate results, thus reducing the risk of sample compression (i.e. in the case of foams).

Sample identification, data input/output and reporting

The large backlit display (four lines by forty characters), together with the alpha-numeric keyboard, enables simple and quick set-up of all the analytical parameters. Furthermore, users can type into the sample information page a detailed description of the material under test including comments. For the benefit of highly regulated laboratories all this information is then printed along with the sample results. All the analytical, calibration and communication/reporting parameters can be easily edited to optimize the performance. Pycnomatic can be connected directly to a balance, a printer and a computer, so the report is generated automatically at the end of the experiment and printed or sent to the computer in electronic editable format. Finally, a dedicated software displays all the phases of the measurement and automatically saves data files of up to ten repeated experiments.





The first density analyzer with fully integrated temperature control: fastest results and unmatched accuracy

In gas pycnometry the speed of analysis is mainly limited by the time taken to reach the thermal stability and by the required level of reproducibility in the determination of sample volume. The innovative and powerful temperature control of the Pycnomatic is based on a built-in powerful Peltier device that dramatically reduces the time necessary to achieve the thermal

Reference volume

stability of the sample. The user obtains a very high level of precision in a matter of minutes. The ability of the system to reach the thermal equilibrium quickly is of particular benefit when a high sample throughput is required. The Pycnomatic avoids both long dead times and a high number of purging cycles before the test.

Pycnomatic-Density Measurement Report Sample name Cement powder Comment Dried at 100 °C in oven for 30 minutes Operator Analysis start 23.01.05 11:26 Analysis end 23.01.05 11:57 Vessel Correction 0.00000 cc Vessel ID no. 1 Vessel weight 3.123000 g Total weight before 31.80300 g Sample weight before 28.68000 g Total weight after 28.68000 g Sample weight after 28.68000 g Weight difference 0.00000 g **Analytical Paramters**

21.16887 cc (I)

Stop calibrating and start measuring!

Environmental temperature changes continuously, thus in non-temperature controlled analyzers precision and reproducibility in density tests are not assured unless the instrument calibration is repeated regularly. Pycnomatic offers a built-in extremely precise, powerful and fast response temperature control system. The reference and sample chambers, the manifold and the pressure transducer are all maintained at a constant temperature, chosen by the operator with a precision of +/- 0.01 °C. The user chooses the Pycnomatic temperature in the range from 18.00 °C to 35.00 °C avoiding any effect on internal volume changes that can occur due to room temperature fluctuations. Want precision? With Pycnomatic you can finally start measuring your samples and eliminate continuous re-calibrations!

Cell volume	29.14182 cc									
Filler volume	0.00000 cc									
Repeated analyses no.	3	Measure	Measurement Raw Data							
Flow cleaning time	60 sec	Patmh	Prh	Pch	Temp	Volume	Aver. Vol	Aver. Dev.		
Number of cleaning cycles	3	kPa	kPa	kPa	°C	CC	CC	CC		
Sample cleaning time	10 sec	100.440	201.056	152.652	19.99	9.51641	9.51641	0.00000		
Atm stabilization time	30 sec	100.441	200.977	152.611	19.99	9.51696	9.51668	0.00039		
Restriction delta presure	150.000 kPa	100.441	200.974	152.610	19.99	9.51712	9.51683	0.00038		
Equilibrium delta pressure	0.010 kPa	100.438	201.048	152.649	19.99	9.51790	9.51733	0.00051		
Equilibrium delta time	10 sec	100.436	200.970	152.606	19.99	9.51769	9.51757	0.00040		
Standard deviation %	0.003 %	100.436	201.044	152.646	19.99	9.51856	9.51805	0.00046		
No. of good measurements	3	100.436	200.966	152.606	19.99	9.51824	9.51816	0.00044		
No. of max measurements	100	100.436	201.027	152.636	19.99	9.51735	9.51805	0.00063		
Temperature set	20.00 °C	100.436	201.028	152.638	19.99	9.51870	9.51810	0.00069		
Reculte		100.434	201.048	152.646	19.99	9.51755	9.51786	0.00073		
	0 51707 00	100.430	201.308	152.778	19.99	9.51672	9.51765	0.00100		
Volume standard deviation	9.01/9/00	100.425	201.024	152.630	19.99	9.51817	9.51748	0.00073		
Volume standard deviation on volume		100.423	201.042	152.637	19.99	9.51727	9.51738	0.00073		
% Stanuaru ueviation on volume		100.420	201.019	152.626	19.99	9.51914	9.51819	0.00094		
Average sample Density	3.01325 y/cc	100.418	201.019	152.626	19.99	9.51933	9.51858	0.00114		
0/ Standard deviation on density	0.00009 g/cc	100.418	201.017	152.623	19.99	9.51824	9.51890	0.00058		
% Standard deviation on density		100.419	201.024	152.628	19.99	9.51890	9.51882	0.00055		
Average sample density after	3.01325 g/cc	100.419	201.025	152.627	19.99	9.51784	9.51833	0.00054		
		100.419	201.360	152.802	19.99	9.51828	9.51834	0.00054		
		100 420	201.028	152,629	19.99	9.51778	9.51797	0.00027		

Laboratory Solutions Backed by Worldwide Service and Support

Tap our expertise throughout the life of your instrument. Thermo Scientific Services extends its support throughout our worldwide network of highly trained and certified engineers who are experts in laboratory technologies and applications. Put our team of experts to work for you in a range of disciplines – from system installation, training and technical support, to complete asset management and regulatory compliance consulting. Improve your productivity and lower the cost of instrument ownership through our product support services. Maximize uptime while eliminating the uncontrollable cost of unplanned maintenance and repairs. When it's time to enhance your system, we also offer certified parts and a range of accessories and consumables suited to your application.

To learn more about our products and comprehensive service offerings, visit us at www.thermo.com.

In addition to these offices, Thermo Fisher Scientific maintains a network of representative organizations throughout the world.

Australia

+61 2 8844 9500 * analyze.au@thermo.com **Austria** +43 1 333 50340 * analyze.at@thermo.com

Belgium +32 2 482 30 30 • analyze.be@thermo.com

Canada

+1 800 532 4752 • analyze.ca@thermo.com
China

+86 10 5850 3588 • analyze.cn@thermo.com Denmark

+45 70 23 62 60 • analyze.dk@thermo.com France

33 1 60 92 48 00 ° analyze.fr@thermo.com

Germany +49 6103 408 1014 • analyze.de@thermo.com India

+91 22 6742 9434 • analyze.in@thermo.com Italy_____

+39[°]02 950 591 • analyze.it@thermo.com Japan

+81 45 453 9100 • analyze.jp@thermo.com

Latin America +1 608 276 5659 * analyze.la@thermo.com Netherlands_____

+31 76 587 98 88 • analyze.nl@thermo.com South Africa

+27 11 570 1840 • analyze.sa@thermo.com

Spain +34 91 657 4930 • analyze.es@thermo.com

Sweden / Norway / Finland +46 8 556 468 00 • analyze.se@thermo.c

Switzerland

+41 61 48784 00 • analyze.ch@thermo.com

+44 1442 233555 • analyze.uk@thermo.com USA

+1 800 532 4752 • analyze.us@thermo.com

www.thermo.com

ISO 9001

Thermo Electron S.p.A., Milan, Italy is ISO Certified.

©2007 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Electron Corporation and its subsidiaries.

Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

BR11011_E 12/06C

